


Order and Quote Form

Premium Threshold - With Sill Only

AA Wave Grate & Ti Tile Insert Grate Styles



Select Grate Style



AA
Wave Grate

Wave Grate Colour Finish

Satin/ Aluminium

Matte Black

Beach Gold



Ti
Tile Insert

Tile Thickness
*For tile insert
grate style only

Tiles up to 10mm thick

Tiles up to 16mm thick (Additional Charge Applies)

Tiles up to 20mm thick (Additional Charge Applies)

Grate Width


65mm (Only available for Tile Insert)

(Minimum door track depth 35mm) O/A Width = 81mm + Door Track Width

100mm

(Minimum door track depth 30mm) O/A Width = 115mm + Door Track Width

Channel + Door Track Dimensions



Length + Outlet Requirements

Please include drainage length and all required outlets.

Required Outlet Size

65 & 100mm Grates	32mm	38mm	44mm	51mm
100mm Grates only	63mm	76mm	89mm	

Optional Components (Additional Charges Apply)

Concrete Ties (17mm wide / 10mm hole, extend 30mm from base)


Stainless Steel Packer (5mm Thickness)

Electropolishing (recommended for installation in marine or pool area environments)

Overflow Outlet

PLEASE NOTE Minimum channel length equals door track length plus 6mm. Grates longer than 1500mm and Tile Inserts longer than 1200mm are supplied in multiple sections. Channels 2950mm maximum in one piece, channels over 2950mm are supplied in multiple sections with joiner. See AS3500 standard & local regulator for specific outlet & drainage requirements.

+/- 2mm tolerance on dimensions.



Full Name

Email Address

Company Name

Order Number

Stormtech Quote Number

Telephone

Signature